

## ERRATA FOR "ENGINEERING NOISE CONTROL" 2nd Edn., 5th printing

March 24, 2002

p26, Equation (1.49) should be:

$$p(\mathbf{r}, t) = P(\mathbf{r})e^{jk(\mathbf{c}\mathbf{r} + |\mathbf{r}| + \theta/k)} = P(\mathbf{r})e^{j(\omega t + \theta_p(\mathbf{r}))} = Ae^{j\omega t} \quad (1.49)$$

p106, Figure 4.3 caption, change "100" to "1000"

p108, 10 lines after equation 4.23, change "3/5 and 3/4" to "3/4 and 3/5"

p109, After equation 4.28 add, "If the actual exposure time is greater than eight hours, then replace the "8" in the above equation with the actual exposure time (in hours)."

p110 3<sup>rd</sup> line, " $T_A$ " should be  $T_a$

p114, Figure 4.6 caption, change "S3.1-1977" to "S3.14-1977"

p114 6<sup>th</sup> line from top, change "and 2000Hz" to "2000Hz and 4000Hz" and change "three octave bands" to "four octave bands"

p137, 3 lines above equation 5.41, remove "By introducing the constant 1/3 and"

p137, line above equation 5.41, replace "(1995)" with "(1955)"

p144, In equation 5.70 and in the line above the equation, change  $W$  to  $W_t$

p165, Equation 5.143, the quantity "erfc" should not be in italics as it is the error function

p165, Immediately after equation 5.143, add "where erfc is the error function"

p170, 13<sup>th</sup> line under section 5.11.3, " $D_{IM}$ " should be " $DI_M$ "

p171, 3<sup>rd</sup> line from the top of the page, " $D_{IM}$ " should be " $DI_M$ "

p174, The slope of the curve in figure 5.14(b) is incorrect. The start point at the bottom of the graph is correct and the graph is a straight line passing through the point (20,4)

p177, Figure 5.17, the labels for the 63Hz and 200 Hz curves should be interchanged.

p211, In equation 6.20, there should be a subscript "1" on the  $r$  on the left hand side and a subscript "2" on the  $r$  on the right hand side

p214, In Table 6.3, " $S_1$ " should be " $S$ "

p215, equation 6.29, replace " $(S\bar{\alpha})$ " with " $(S_R\bar{\alpha})$ " and in the line below the equation, replace " $S$ " with  $S_R$

p226, Equation 7.6, replace “ $k^2$ ” with “ $k_z^2$ ”

p231, In equation 7.22,  $\delta/2\pi$  should be  $\delta/\pi$

p249, fig 7.6, y-axis label should be changed from  $\bar{\alpha}$  to  $\alpha_{st}$

p 254, equation 7.73 should be

$$\bar{\alpha} = \frac{4V\pi f}{Sc} \left[ \left| \left( \eta_A + \eta_{pA} \left( 1 + \frac{n_p}{n_A} \right) + \eta_{pT} \right) - \left[ \left( \eta_A + \eta_{pA} \left( \frac{n_p}{n_A} - 1 \right) - \eta_{pT} \right)^2 + 4 \frac{n_p}{n_A} \eta_{pA}^2 \right]^{1/2} \right| - 2\eta_A \right]$$

p254, 4 lines under equation 7.73, the expression for  $\eta_{pA}$  should be  $\eta_{pA} = \rho c \sigma / 2\pi f m$

p254, Replace the line above Equation (7.74) and Equations 7.74 - 7.76 with:

For frequencies above twice the resonance frequency of the lowest order mode (see Equation (8.18)), the panel radiation ratio  $\sigma$  may be calculated using the following equations (Maidanik, 1962, Price and Crocker, 1970). Above twice the fundamental resonance frequency of the panel and below the critical frequency:

$$\sigma = \left( \frac{2c^2}{f_c^2 A_p} g_1(\alpha) + \frac{Pc}{f_c A_p} g_2(\alpha) \right) \gamma ; \quad 2f_{1,1} < f < 0.99f_c \quad (7.74a)$$

where,

$$g_1(\alpha) = \begin{cases} \frac{4}{\pi^4} \frac{(1 - 2\alpha^2)}{\alpha(1 - \alpha^2)^{1/2}}; & f < f_c/2 \\ 0; & f > f_c/2 \end{cases} \quad (7.74b)$$

$$g_2(\alpha) = \frac{1}{4\pi^2} \left[ \frac{(1 - \alpha^2) \log_e \left( \frac{1 + \alpha}{1 - \alpha} \right) + 2\alpha}{(1 - \alpha^2)^{3/2}} \right] \quad (7.74c)$$

Close to the critical frequency, the radiation ratio is:

$$\sigma \approx \sqrt{\frac{L_x f_c}{c}} + \sqrt{\frac{L_y f_c}{c}} ; \quad 0.99f_c < f < 1.01f_c \quad (7.75)$$

Above the critical frequency, the radiation ratio is:

$$\sigma = \left( 1 - \frac{f_c}{f} \right)^{-1/2} ; \quad f > 1.01f_c \quad (7.76a)$$

Below the first resonance frequency of the panel,  $f_{1,1}$ , defined by Equation (8.21), the radiation ratio is (Beranek (1988):

$$\sigma = \frac{4A_p}{c^2} f^2 \quad (7.76b)$$

Between the lowest order modal resonance and twice that frequency, the radiation ratio is found by interpolating linearly (on a  $\log \sigma$  vs  $\log f$  plot).

p261, Interchange figure 7.11 with figure 7.16 on page 269, but leave the figure captions where they are now.

p264, In Table 7.2, interchange  $\beta_1$  and  $\beta_2$

p266, Equation 7.100 should be:

$$\langle p^2(\mathbf{r}) \rangle = \frac{W\rho c}{4\pi} \left[ \frac{1}{r^2} + \sum_{m=1}^{\infty} \sum_{n=1}^{\infty} \frac{4\beta^{m+n}}{(ma)^2 + (nb)^2 + r^2} + \sum_{n=1}^{\infty} \frac{2\beta^n}{(nb)^2 + r^2} + \sum_{m=1}^{\infty} \frac{2\beta^m}{(ma)^2 + r^2} \right]$$

p266, The y-axis label in figure 7.14 should read  $10\log_{10}\langle p^2(\mathbf{r}) \rangle - 10\log_{10}(W\rho c/\pi a^2)$

p268, 6<sup>th</sup> line from the bottom of the page, "30 dB" should be "9 dB"

p269, 5<sup>th</sup> line under figure caption, change "strength" to "power"

p269, In equation 7.107, change "z" to "r"

p271, The heading "**Optimising reverberation control**" should be "**Optimising reverberation times**"

p286, in equations 8.26 and 8.27, replace "5" with "5.5"

p287, in first equation in figure 8.6 caption replace "53" with "54"

p288, Equation, 8.29, first line, "- 20log" should be "+ 20log"

p288, Equation, 8.29, second line, "+ 10log" should be "- 10log"

p293, 3<sup>rd</sup> equation, all the "1" subscripts should be replaced with "2"

p293, In the figure, on the x-axis, " $0.5f_{c1}$ " should be " $0.5f_{c2}$ "

p294, Remove  $\beta$  from the denominator of equation (8.42)

p294, Replace " $D = 2$  if  $f < f_{c1}$  and  $f_{c2}$ " with " $D = 2/\beta$  if  $f < 0.9 \times \min(f_{c1}$  and  $f_{c2})$ ";

p295, 2 lines above equation (8.47), change "0.05" to "0.1 to 0.15"

p295, 2 lines above equation 8.48, delete "the stud is assumed rigid and" and replace equation (8.48) with

$$\tau_F = \frac{\pi(\xi_1 + \xi_2)n}{4\bar{\alpha}_1^2 \bar{\alpha}_2^2 \eta_1 \eta_2 \xi_1 \xi_2 (n^2 + \nu^2) \bar{\alpha}^2} + \frac{64\rho^2 c^3 D}{\left[ g^2 + \left( 4(2\pi f)^{3/2} m_1 m_2 c C_M - g \right)^2 \right] b (2\pi f)^2}$$

p295, first line after equation (8.52), insert after the word "panels" the following:; " $\bar{\alpha}$  is the Sabine absorption coefficient of the acoustic material in the cavity between the two walls"

p313, second line of the solution, change "1" to "1.1"

p325, first line after equation 8.75, replace "b" with "b (> $\lambda/2$ )"

p330, Equation 8.79, third line, "a" should be " $\alpha$ "

p334, in equation 8.90, "16.3" should be "226" and (m/h) should be (m/h)<sup>1/2</sup>

p346, first line under equation 9.17, replace "q > a" with "q > 2a"

p346, equation 9.18, replace "0.44" with "0.43"

p346, In equation 9.19, replace "d" with "t" in two places; in the line above equation 9.20, replace "d" with "t"; in equation 9.20, replace "d" with "t"; and 5 lines from the bottom of the page, replace "d" with "t".

p350, Line beneath equation 9.27, replace "reactive impedance" with "square root of the product of the inductive and capacitive impedances"

p357, Section 9.7.4, item 1, change U to U<sub>0</sub>

p375, Top line, change "h" to "2h"

p375, R<sub>1</sub>l/ρ<sub>c</sub> should be R<sub>1</sub>l/ρ<sub>c</sub>

p389, After the first equation, add "where A<sub>2</sub>/A<sub>1</sub> is the ratio of the total duct cross sectional area to the open cross sectional area"

p393, In equation 9.92, "f < f<sub>cr</sub>" should be "f ≥ f<sub>cr</sub>"

p393, First line after equation 9.94, "f<sub>1</sub>" should be "f<sub>0</sub>" in two places

p393, Line above equation 9.96, "f<sub>1</sub>" should be "f<sub>0</sub>"

p393, In equation 9.95b, replace l with L in two places; also in the line two above equation 9.94

p397, 2 lines above equation 9.102, (P<sub>M</sub><sup>2</sup>) should be ⟨p<sub>M</sub><sup>2</sup>⟩

- p398, line 2, replace “at location” with “at a location”
- p398, 2<sup>nd</sup> line from bottom of page, interchange the symbols “ $r$ ” and “ $r_0$ ”
- p408, 9<sup>th</sup> line from bottom of page, replace “two rocking mode” with “rocking and horizontal”
- p408, 8<sup>th</sup> line from bottom of page, replace “roll and pitch” with “roll and horizontal motion”
- p409. Fig 10.5 caption, change “Q” to “ $\Omega$ ”
- p410, 2<sup>nd</sup> line, add after “10.4)” the phrase, “and with  $\delta$  now the radius of gyration for rotation about the x-axis”
- p418, replace “ $i$ ” everywhere with “ $j$ ” in equation 10.21
- p418, 2<sup>nd</sup> line after equation 10.21, add “ $f_1$ ” after “frequency”
- p419, 3<sup>rd</sup> line under equation 10.24, add “ $y$  is the amplitude of mass  $m_2$ ” after “10.5)”
- p419, 14<sup>th</sup> line under 10.6, “ $d/\omega^2 = v/\omega = a$ ” should be “ $d\omega^2 = v\omega = a$ ”
- p430, In equation 10.36b, replace “4” with “2” and in equation 10.36c delete the “2”
- p431. 6<sup>th</sup> dot point, change “controls” to “control”
- p434, Replace Equation 11.1 with:
- $$L_w = C_F + 10 \log_{10} Q + 20 \log_{10} P - E/3 + 18 \text{ dB re } 10^{-12} \text{ W} \quad (11.1)$$
- p454, first line under equation 11.38, add after “ $G_f$ ”, the phrase, “upstream of the valve”
- p456, In equations 11.54 and 11.55, “ $f_0$ ” should be “ $f_{co}$ ” in two places in each equation
- p457, In equation 11.56, “ $f_0$ ” should be “ $f_{co}$ ” in two places
- p462, Table 11.18 caption, replace “Equation 11.47” with “Equation 11.68”
- p465, Equations (11.71), (11.72) and (11.74) should be replaced respectively with the following equations:
- $$L_p = 44 \log_{10} U + 17 \log_{10} \dot{m} + 44 \quad (\text{dB re } 20 \text{ } \mu\text{Pa})$$
- $$L_w = 44 \log_{10} U + 17 \log_{10} \dot{m} + 53 \quad (\text{dB re } 10^{-12} \text{ W})$$
- $$W_a = 4.2 \eta \dot{M} H \quad (\text{W})$$
- p517, In equation C7, change “ $a(X_1)$ ” to “ $0.592 a(X_1)$ ”

p526, The second "cos  $\theta$ " in Equation (E.3) should be deleted.

p527, In equation E.6, change the minus sign to a plus sign.

p528, 2<sup>nd</sup> line under equation E7, add the words, "including the porous liner" after "cavity"

p548, The Clifford reference should be "1973", not "1983"

p574, add to list of symbols, " $K_1()$  Modified Hankel function (Chapter 7)"